



## HOT ROLLED BARS

---

- HOT ROLLED ROUNDS
- HOT ROLLED SQUARES
- REINFORCED BARS
- HOT ROLLED STRIP
- HOT ROLLED FLATS
- PLOW STEEL FLATS
- TOLERANCES

# STEEL ROUNDS HOT ROLLED

ASTM A36

1018 SPECIAL QUALITY ASTM A576

1045 SPECIAL QUALITY ASTM A576

Size In Inches	Lbs. Per Ft.	Est. Lbs. Per 20ft Bar	Size In Inches	Lbs. Per Ft.	Est. Lbs. Per 20ft Bar
1/4	0.1669	3.338	2-1/4	13.52	270.4
5/16	0.2608	5.216	2-3/8	15.06	301.2
3/8	0.3755	7.510	2-1/2	16.69	333.8
7/16	0.5111	10.22	2-5/8	18.40	368.0
1/2	0.6676	13.35	2-3/4	20.19	403.8
9/16	0.8449	16.90	2-7/8	22.07	441.4
5/8	1.043	20.86	3	24.03	480.6
3/4	1.502	30.04	3-1/8	26.08	521.6
7/8	2.045	40.90	3-1/4	28.21	564.2
15/16	2.347	46.94	3-3/8	30.42	608.4
1	2.670	53.40	3-1/2	32.71	654.2
1-1/8	3.380	67.60	3-5/8	35.09	701.8
1-1/4	4.173	83.46	3-3/4	37.55	751.0
1-5/16	4.600	92.00	3-7/8	40.10	802.0
1-3/8	5.049	101.0	4	42.73	854.6
1-1/2	6.008	120.2	4-1/8	45.44	908.8
1-5/8	7.052	141.0	4-1/4	48.23	964.6
1-3/4	8.178	163.6	4-3/8	51.11	1022.2
1-7/8	9.388	187.8	4-1/2	54.08	1081.6
2	10.68	213.6	4-5/8	57.12	1142.4
2-1/8	12.06	241.2	4-3/4	60.25	1205.0
Size In Inches	Lbs. Per Ft.	Est. Lbs. Per 20ft Bar	Size In Inches	Lbs. Per Ft.	Est. Lbs. Per 20ft Bar
5	66.76	1335.2	7-3/4	160.4	3208.0
5-1/4	73.60	1472.0	8	170.9	3418.0
5-1/2	80.78	1615.6	8-1/4	181.8	3636.0
5-3/4	88.29	1765.8	8-1/2	192.9	3858.0
6	96.13	1922.6	8-3/4	204.5	4090.0
6-1/8	100.2	2004.0	9	216.3	4326.0
6-1/4	104.3	2086.0	9-1/2	241.0	4820.0
6-1/2	112.8	2256.0	9-3/4	253.9	5078.0
6-3/4	121.7	2434.0	10	267.0	5340.0
7	130.8	2616.0	10 1/2	294.4	5888.0
7-1/4	140.4	2808.0	11	323.0	6460.0
7-1/2	150.2	3004.0			

# STEEL ROUNDS FORGED AND ROUGH TURNED

1018 1045 NOT NORMALIZED

Size In Inches	Suitable for Finishing to	Est. Lbs. Per Ft.	Size In Inches	Suitable for Finishing to	Est. Lbs. Per Ft.
10-3/4	10-1/2	308.6	11-3/4	11-1/2	368.6
11-1/8	10-1/2	330.5	12-1/4	12	400.7
11-1/4	11	337.9	13-1/4	13	468.8
11-5/8	11	360.9	14-1/4	14	542.2

# STEEL SQUARES HOT ROLLED

ASTM A36

1018 SPECIAL QUALITY

ASTM A576

1045 SPECIAL QUALITY

ASTM A576

Size In Inches	Lbs. Per Ft.	Est. Lbs. Per 20ft Bar	Size In Inches	Lbs. Per Ft.	Est. Lbs. Per 20ft Bar
3/8	0.4781	9.562	1-3/4	10.41	208.2
7/16	0.6508	13.02	2	13.60	272.0
1/2	0.8500	17.00	2-1/4	17.21	344.2
9/16	1.076	21.52	2-1/2	21.25	425.0
5/8	1.328	26.56	2-3/4	25.71	514.2
3/4	1.913	38.26	3	30.60	612.0
7/8	2.603	52.06	3-1/2	41.65	833.0
1	3.400	68.00	4	54.40	1088.0
1-1/8	4.303	86.06	4-1/2	68.85	1377.0
1-1/4	5.313	106.3	5	85.00	1700.0
1-3/8	6.428	128.6	6	122.40	2448.0
1-1/2	7.650	153.0			

GALVANIZED-All Hot Rolled Rounds and Squares can be furnished Galvanized when required.

# CONCRETE REINFORCING BARS

STOCK LENGTHS 20', 40'

MATERIAL AVAILABLE IN GRADES 40 AND 60

Size Bar (Inches)	Bar Number	Wt./Ft. Pounds (Per Ft.)
1/4 Rd.	2	0.167
3/8 Rd.	3	0.376
1/2 Rd.	4	0.668
5/8 Rd.	5	1.043
3/4 Rd.	6	1.502
7/8 Rd.	7	2.044
1 Rd.	8	2.670
1-1/8 Rd.	9	3.379

Round bars equal in cross sectional area to the standard square sizes indicated. 1/4 is plain round, not deformed.

# HOT ROLLED STRIP BANDS

B.W. Gage and Size Inches	Weight Per Ft. Lbs.	B.W. Gage and Size Inches	Weight Per Ft. Lbs.
<b>1/8 (.125) x</b>		<b>3/16 (.1875") x</b>	
3/8	0.159	3/8	0.239
1/2	0.213	1/2	0.319
5/8	0.266	5/8	0.398
3/4	0.319	3/4	0.478
7/8	0.372	7/8	0.558
1	0.425	1	0.638
1-1/8	0.478	1-1/8	0.717
1-1/4	0.531	1-1/4	0.797
1-3/8	0.584	1-3/8	0.877
1-1/2	0.638	1-1/2	0.956
1-3/4	0.744	1-3/4	1.116
2	0.850	2	1.275
2-1/4	0.956	2-1/4	1.43
2-1/2	1.062	2-1/2	1.59
2-3/4	1.169	2-3/4	1.75
3	1.275	3	1.91
3-1/4	1.381	3-1/4	2.07
3-1/2	1.488	3-1/2	2.23
4	1.700	4	2.55
4-1/2	1.913	4-1/2	2.87
5	2.125	5	3.19
5-1/2	2.338	5-1/2	3.51
6	2.550	6	3.83
7	2.975	7	4.46
8	3.400	8	5.10
		12	7.65

# HOT ROLLED FLATS

ASTM A36

Sizes In Inches	Weight Per Ft. Lbs.	Sizes In Inches	Weight Per Ft. Lbs.
<b>1/4 x</b>		<b>5/16 x</b>	
<b>3/8</b>	0.319	<b>1</b>	1.06
<b>1/2</b>	0.425	<b>1-1/8</b>	1.20
<b>5/8</b>	0.531	<b>1-1/4</b>	1.33
<b>3/4</b>	0.638	<b>1-3/8</b>	1.46
<b>7/8</b>	0.744	<b>1-1/2</b>	1.59
<b>1</b>	0.850	<b>1 3/4</b>	1.86
<b>1-1/8</b>	0.956	<b>2</b>	2.13
<b>1-1/4</b>	1.06	<b>2-1/4</b>	2.39
<b>1-3/8</b>	1.17	<b>2-1/2</b>	2.66
<b>1-1/2</b>	1.28	<b>2-3/4</b>	2.92
<b>1-5/8</b>	1.38	<b>3</b>	3.19
<b>1-3/4</b>	1.49	<b>3-1/4</b>	3.45
<b>2</b>	1.70	<b>3-1/2</b>	3.72
<b>2-1/4</b>	1.91	<b>4</b>	4.25
<b>2-1/2</b>	2.13	<b>4-1/2</b>	4.78
<b>2-3/4</b>	2.34	<b>5</b>	5.31
<b>3</b>	2.55	<b>5-1/2</b>	5.84
<b>3-1/4</b>	2.76	<b>6</b>	6.38
<b>3-1/2</b>	2.98	<b>7</b>	7.44
<b>3-3/4</b>	3.19	<b>7-1/2</b>	7.97
<b>4</b>	3.40	<b>8</b>	8.50
<b>4-1/4</b>	3.61	<b>3/8 x</b>	
<b>4-1/2</b>	3.83	<b>1/2</b>	0.638
<b>5</b>	4.25	<b>5/8</b>	0.797
<b>5-1/2</b>	4.68	<b>3/4</b>	0.956
<b>6</b>	5.10	<b>7/8</b>	1.12
<b>6-1/2</b>	5.53	<b>1</b>	1.28
<b>7</b>	5.95	<b>1-1/8</b>	1.43
<b>7-1/2</b>	6.38	<b>1-1/4</b>	1.59
<b>8</b>	6.80	<b>1-3/8</b>	1.75
<b>5/16 x</b>		<b>1-1/2</b>	1.91
<b>1/2</b>	0.531	<b>1-5/8</b>	2.07
<b>5/8</b>	0.664	<b>1-3/4</b>	2.23
<b>3/4</b>	0.797	<b>2</b>	2.55
<b>7/8</b>	0.93		

# HOT ROLLED FLATS

Sizes In Inches	Weight Per Ft. Lbs.	Sizes In Inches	Weight Per Ft. Lbs.
<b>3/8 x</b>		<b>1/2 x</b>	
<b>2-1/4</b>	2.87	<b>5/8</b>	1.06
<b>2-1/2</b>	3.19	<b>3/4</b>	1.28
<b>2-3/4</b>	3.51	<b>7/8</b>	1.49
<b>3</b>	3.83	<b>1</b>	1.70
<b>3-1/4</b>	4.14	<b>1-1/8</b>	1.91
<b>3-1/2</b>	4.46	<b>1-1/4</b>	2.13
<b>4</b>	5.10	<b>1-3/8</b>	2.34
<b>4-1/2</b>	5.74	<b>1-1/2</b>	2.55
<b>5</b>	6.38	<b>1-5/8</b>	2.76
<b>5-1/2</b>	7.01	<b>1-3/4</b>	2.98
<b>6</b>	7.65	<b>2</b>	3.40
<b>6-1/2</b>	8.29	<b>2-1/4</b>	3.83
<b>7</b>	8.93	<b>2-1/2</b>	4.25
<b>7-1/2</b>	9.56	<b>2-3/4</b>	4.68
<b>8</b>	10.20	<b>3</b>	5.10
<b>7/16 x</b>		<b>3-1/4</b>	5.53
<b>3/4</b>	1.12	<b>3-1/2</b>	5.95
<b>1</b>	1.49	<b>4</b>	6.80
<b>1-1/4</b>	1.86	<b>4-1/2</b>	7.65
<b>1-3/8</b>	2.05	<b>5</b>	8.50
<b>1-1/2</b>	2.23	<b>5-1/4</b>	8.93
<b>1-3/4</b>	2.60	<b>5-1/2</b>	9.35
<b>2</b>	2.98	<b>6</b>	10.20
<b>2-1/4</b>	3.35	<b>7</b>	11.90
<b>2-1/2</b>	3.72	<b>8</b>	13.60
<b>3</b>	4.46	<b>5/8 x</b>	
<b>3-1/2</b>	5.21	<b>3/4</b>	1.59
<b>4</b>	5.95	<b>7/8</b>	1.86
<b>4-1/2</b>	6.69	<b>1</b>	2.13
<b>5</b>	7.44	<b>1-1/8</b>	2.39
<b>5-1/2</b>	8.18	<b>1-1/4</b>	2.66
<b>6</b>	8.93	<b>1-3/8</b>	2.92
		<b>1-1/2</b>	3.19
		<b>1-5/8</b>	3.45

# HOT ROLLED FLATS

Sizes In Inches	Weight Per Ft. Lbs.	Sizes In Inches	Weight Per Ft. Lbs.
5/8 x		3/4 x	
1-3/4	3.72	7	17.85
2	4.25	8	20.40
2-1/4	4.78	7/8 x	
2-1/2	5.31	1	2.98
2-3/4	5.84	1-1/4	3.72
3	6.38	1-3/8	4.09
3-1/4	6.91	1-1/2	4.46
3-1/2	7.44	1-3/4	5.21
4	8.50	2	5.95
4-1/2	9.56	2-1/4	6.69
5	10.63	2-1/2	7.44
5-1/2	11.69	2-3/4	8.18
6	12.75	3	8.93
7	14.88	3-1/2	10.41
8	17.00	4	11.90
3/4 x		4-1/2	13.39
7/8	2.23	5	14.88
1	2.55	5-1/2	16.36
1-1/8	2.87	6	17.85
1-1/4	3.19	7	20.83
1-1/2	3.83	8	23.80
1-5/8	4.14	1 x	
1-3/4	4.46	1-1/4	4.25
2	5.10	1-1/2	5.10
2-1/4	5.74	1-3/4	5.95
2-1/2	6.38	2	6.80
2-3/4	7.01	2-1/4	7.65
3	7.65	2-1/2	8.50
3-1/4	8.29	2-3/4	9.35
3-1/2	8.93	3	10.20
4	10.20	3-1/4	11.05
4-1/2	11.48	3-1/2	11.90
5	12.75	4	13.60
5-1/2	14.03	4-1/2	15.30
6	15.30	5	17.00
		5-1/2	18.70

# HOT ROLLED FLATS

Gage and Sizes In Inches	Weight Per Ft. Lbs.	Gage and Sizes In Inches	Weight Per Ft. Lbs.
1 x		1-1/2 x	
6	20.40	5	25.50
7	23.80	5-1/2	28.05
8	27.20	6	30.60
1-1/8 x		7	35.70
2	7.65	*8	40.80
3	11.48	1-3/4 x	
4	15.30	2	11.90
5	19.13	2-1/2	14.88
6	22.95	3	17.85
1-1/4 x		3-1/2	20.83
1-1/2	6.38	4	23.80
1-3/4	7.44	4-1/2	26.78
2	8.50	5	29.75
2-1/4	9.56	5-1/2	32.73
2-1/2	10.63	6	35.70
2-3/4	11.69	2x	
3	12.75	2-1/2	17.00
3-1/4	13.81	3	20.40
3-1/2	14.88	3-1/2	23.80
4	17.00	4	27.20
4-1/2	19.13	4-1/2	30.60
5	21.25	5	34.00
5-1/2	23.37	*6	40.80
6	25.50	*7	47.60
7	29.75	*8	54.40
8	34.00	2-1/2 x	
1-1/2 x		3	25.50
1-3/4	8.93	3-1/2	29.75
2	10.20	4	34.00
2-1/4	11.48	4-1/2	38.25
2-1/2	12.75	*5	42.50
2-3/4	14.03	*6	51.00
3	15.30	3 x	
3-1/2	17.85	*4	40.80
4	20.40	*4-1/2	45.90
4-1/2	22.95	*5	51.00
		*6	61.20

\*Special Quality C1018

# PLOW STEEL and M1044 FLATS

WIDTHS OVER 8' ARE CLASSED AS PLATES BUT ARE LISTED HERE WITH FLAT BARS FOR CONVENIENCE. STOCK LENGTHS 20'

Sizes In Inches	Weight Per Ft. Lbs.	Est. Wt. 20' Bar	Sizes In Inches	Weight Per Ft. Lbs.	Est. Wt. 20' Bar
<b>1/4 x</b>			<b>1/2 x</b>		
<b>1</b>	.8508	17.02	<b>5/8</b>	1.064	21.27
<b>1-1/4</b>	1.064	21.27	<b>3/4</b>	1.276	25.52
<b>1-1/2</b>	1.276	25.52	<b>1</b>	1.702	34.03
<b>2</b>	1.702	34.03	<b>1-1/4</b>	2.127	42.54
<b>2-1/2</b>	2.127	42.54	<b>1-1/2</b>	2.552	51.05
<b>3</b>	2.552	51.05	<b>1-3/4</b>	2.978	59.56
<b>3-1/2</b>	2.978	59.56	<b>2</b>	3.403	68.06
<b>4</b>	3.403	68.06	<b>2-1/4</b>	3.829	76.57
<b>5</b>	4.254	85.08	<b>2-1/2</b>	4.254	85.08
<b>6</b>	5.105	102.1	<b>3</b>	5.105	102.1
<b>8</b>	6.806	136.1	<b>3-1/2</b>	5.956	119.1
<b>10</b>	8.508	170.2	<b>4</b>	6.806	136.1
<b>12</b>	10.21	204.2	<b>4-1/2</b>	7.657	153.1
<b>14</b>	11.91	238.2	<b>5</b>	8.508	170.2
<b>5/16 x</b>			<b>6</b>	10.21	204.2
<b>1-1/4</b>	1.329	26.59	<b>8</b>	13.61	272.3
<b>1-1/2</b>	1.595	31.91	<b>10</b>	17.02	340.3
<b>2</b>	2.127	42.54	<b>12</b>	20.42	408.4
<b>2-1/2</b>	2.659	53.18	<b>16</b>	27.22	544.5
<b>3</b>	3.191	63.81	<b>5/8 x</b>		
<b>4</b>	4.254	85.08	<b>1</b>	2.127	42.54
<b>6</b>	6.381	127.6	<b>1-1/4</b>	2.659	53.18
<b>12</b>	12.76	255.2	<b>1-1/2</b>	3.191	63.81
<b>3/8 x</b>			<b>1-3/4</b>	3.722	74.45
<b>1</b>	1.276	25.52	<b>2</b>	4.254	85.08
<b>1-1/4</b>	1.595	31.91	<b>2-1/2</b>	5.318	106.4
<b>1-1/2</b>	1.914	38.29	<b>3</b>	6.381	127.6
<b>1-3/4</b>	2.233	44.67	<b>3-1/2</b>	7.445	148.9
<b>2</b>	2.552	51.05	<b>4</b>	8.508	170.2
<b>2-1/4</b>	2.871	57.43	<b>4-1/2</b>	9.572	191.4
<b>3</b>	3.829	76.57	<b>5</b>	10.64	212.7
<b>3-1/2</b>	4.467	89.33	<b>6</b>	12.76	255.2
<b>4</b>	5.105	102.1	<b>8</b>	17.02	340.3
<b>5</b>	6.381	127.6	<b>10</b>	21.27	425.4
<b>6</b>	7.657	153.1	<b>12</b>	25.52	510.5
<b>8</b>	10.21	204.2			
<b>10</b>	12.76	255.2			
<b>12</b>	15.31	306.3			
<b>14</b>	17.87	357.3			

# PLOW STEEL and M1044 FLATS Continued

Sizes In Inches	Weight Per Ft. Lbs.	Est. Wt. 20' Bar	Sizes In Inches	Weight Per Ft. Lbs.	Est. Wt. 20' Bar
<b>3/4 x</b>			<b>1-1/4 x</b>		
<b>1</b>	2.552	51.05	<b>1-3/4</b>	7.445	148.9
<b>1-1/4</b>	3.191	63.81	<b>2</b>	8.508	170.2
<b>1-1/2</b>	3.829	76.57	<b>2-1/2</b>	10.64	212.7
<b>1-3/4</b>	4.467	89.33	<b>3</b>	12.76	255.2
<b>2</b>	5.105	102.1	<b>3-1/2</b>	14.89	297.8
<b>2-1/4</b>	5.743	114.9	<b>4</b>	17.02	340.3
<b>2-1/2</b>	6.381	127.6	<b>4-1/2</b>	19.14	382.9
<b>3</b>	7.657	153.1	<b>5</b>	21.27	425.4
<b>3-1/2</b>	8.933	178.7	<b>6</b>	25.52	510.5
<b>4</b>	10.21	204.2	<b>8</b>	34.03	680.6
<b>4-1/2</b>	11.49	229.7	<b>10</b>	42.54	850.8
<b>5</b>	12.76	255.2	<b>14</b>	59.56	1191
<b>6</b>	15.31	306.3	<b>1-1/2 x</b>		
<b>8</b>	20.42	408.4	<b>2</b>	10.21	204.2
<b>10</b>	25.52	510.5	<b>2-1/2</b>	12.76	255.2
<b>12</b>	30.63	612.6	<b>3</b>	15.31	306.3
<b>14</b>	35.73	714.7	<b>3-1/2</b>	17.87	357.3
<b>16</b>	40.84	816.7	<b>4</b>	20.42	408.4
<b>7/8 x</b>			<b>4-1/2</b>	22.97	459.4
<b>1</b>	2.978	59.56	<b>5</b>	25.52	510.5
<b>1-1/2</b>	4.467	89.33	<b>6</b>	30.63	612.6
<b>2</b>	5.956	119.1	<b>8</b>	40.84	816.8
<b>2-1/2</b>	7.445	148.9	<b>10</b>	51.05	1021
<b>3</b>	8.933	178.7	<b>14</b>	71.47	1429
<b>3-1/2</b>	10.42	208.4	<b>16</b>	81.68	1634
<b>4</b>	11.91	238.2	<b>1-3/4 x</b>		
<b>4-1/2</b>	13.40	268.0	<b>6</b>	35.73	714.7
<b>5</b>	14.89	297.8	<b>2 x</b>		
<b>6</b>	17.87	357.3	<b>2-1/2</b>	17.02	340.3
<b>1 x</b>			<b>3</b>	20.42	408.4
<b>1-1/2</b>	5.105	102.1	<b>3-1/2</b>	23.82	476.4
<b>2</b>	6.806	136.1	<b>4</b>	27.23	544.5
<b>2-1/2</b>	8.508	170.2	<b>4-1/2</b>	30.63	612.6
<b>3</b>	10.21	204.2	<b>5</b>	34.03	680.6
<b>3-1/4</b>	11.06	221.2	<b>6</b>	40.84	816.8
<b>3-1/2</b>	11.91	238.2	<b>2-1/2 x</b>		
<b>4</b>	13.61	272.3	<b>3</b>	25.52	510.5
<b>4-1/2</b>	15.31	306.3	<b>4</b>	34.03	680.6
<b>5</b>	17.02	340.3	<b>4-1/2</b>	38.29	765.7
<b>6</b>	20.42	408.4	<b>5</b>	42.54	850.8
<b>8</b>	27.23	544.5	<b>6</b>	51.05	1021
<b>10</b>	34.03	680.6	<b>3 x</b>		
<b>12</b>	40.84	816.8	<b>3-1/2</b>	35.73	714.7
<b>14</b>	47.64	952.9	<b>4</b>	40.84	816.8
<b>16</b>	54.45	1089	<b>5</b>	51.05	1021

# HOT ROLL STEEL BARS SIZE TOLERANCES AND OUT-OF-ROUND OR OUT-OF SQUARE TOLERANCES

Hot Rolled Steel Bars Round, Square, and Round-Cornered Square

Specified Sizes (Inches)	Over	Under	Out-of-Round or Out-of-Square section (Inches)
1/2 thru 5/8	0.007	0.007	0.010
Over 5/8 thru 7/8	0.008	0.008	0.012
Over 7/8 thru 1	0.009	0.009	0.013
Over 1 thru 1-1/8	0.010	0.010	0.015
Over 1-1/8 thru 1-1/4	0.011	0.011	0.016
Over 1-1/4 thru 1-3/8	0.012	0.012	0.018
Over 1-3/8 thru 1-1/2	0.014	0.014	0.021
Over 1-1/2 thru 2	1/64	1/64	0.023
Over 2 thru 2-1/2	1/32	0	0.023
Over 2-1/2 thru 3-1/2	3/64	0	0.035
Over 3-1/2 thru 4-1/2	1/16	0	0.046
Over 4-1/2 thru 5-1/2	5/64	0	0.058
Over 5-1/2 thru 6-1/2	1/8	0	0.070
Over 6-1/2 thru 8-1/4	5/32	0	0.085
Over 8-1/4 thru 9-1/2	3/16	0	0.100
Over 9-1/2 thru 10	1/4	0	0.120

\*Out-of-round is the difference between the maximum and minimum diameters of the bar, measured at the same transverse cross section. Out-of-square section is the difference in perpendicular distance between opposite faces, measured at the same transverse cross section.

# SQUARE EDGE AND ROUND EDGE FLATS

Tolerances apply to thickness in inches

Specified Widths (Inches)	Variations from thickness, for thicknesses given over and under (Inches)						Variations from Width (Inches)		
	0.203 up to 0.230	0.230 up to 1/4	1/4 thru 1/2	Over 1/2 thru 1	Over 1 thru 2	Over 2 thru 3	Over 3	Over 3	Under
Up thru 1	.007	.007	.008	.010				1/64	1/64
Over 1 thru 2	.007	.007	.012	.015	1/32			1/32	1/32
Over 2 thru 4	.008	.008	.015	.020	1/32	3/64	3/64	1/16	1/32
Over 4 thru 6	.009	.009	.015	.020	1/32	3/64	3/64	3/32	1/16
Over 6 thru 8	*	.015	.018	.025	1/32	3/64	1/16	1/8	3/32**

\*Flats over 6" thru 8" in width are not available as hot-rolled carbon steel bars in thickness under 0.230".

\*\*For flats over 6" thru 8" in width and thru 3" in thickness.